

(51) International Patent Classification ⁵ : A61M 5/158, 5/32	A1	(11) International Publication Number: WO 92/04062
		(43) International Publication Date: 19 March 1992 (19.03.92)

Published
With international search report.
With amended claims.

Fig. 1 is a perspective view of a wedge-shaped tool. It features a sharp cutting edge labeled 3, a back edge labeled 2, a top edge labeled 1, a side edge labeled 6, and a bottom edge labeled 7. The tool is shown in a perspective view, highlighting its three-dimensional shape.

An intravenous cannula (1) with a bevelled point (2) is designed so as to make the cutting edge (3) of point (2) extend along the portion of the cannula (1) wall which is intended to lie furthest away from the skin (8) in use. The cutting edge (3) is preferably placed along the light opening (6) of cannula (5).

+ DESIGNATIONS OF "SU"

Any designation of "SU" has effect in the Russian Federation. It is not yet known whether any such designation has effect in other States of the former Soviet Union.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU ⁺	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TC	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark				

A cannula.

The present invention relates to a cannula, preferably an intravenous cannula of the kind that has a bevelled point forming a cutting edge.

At present, there is a variety of cannulae on the market, however, they only differ in details as regards connection with tubing, medicament wells, and the like.

It is common to all these cannulae that the cutting edge of the cannula is provided along a portion of the cannula circumference and, also, along the portion of the cannula circumference which is intended to lie closest to the skin when in use.

With correct use and correct equipment complications will generally be avoided when, especially peripheral veins are punctured and cannulated, however, some cases of complications or accidents will be unavoidable.

If the cannula is inserted into the vene in a too steep or vigorous manner, there is a hazard of the opposite vene wall being punctured as well. Such a puncture may, in turn, cause blood to ooze from the vene to the tissue with a consequent haematoma.

Also, medicaments may be injected into areas outside the vene in stead of into the blood stream, because the introduced plastic tube is provided adjacent to the unintended place of puncture. Furthermore, the inserted plastic tube may unintentionally be perforated by unintended movement of the cannula in the tube in connection with removal.

Among known technology, we refer to EP 0 238 419 A3 and EP 0 271 775 A3, DE-OS 24 34 618, GP-PS 1 298 707, and US-PS

2 748 769.

All cited documents disclose straight cannulae or cannulae which are slightly arched at the point, with the cutting edge of the cannula extending along the periphery of the cannula tube, and with the cannula, additionally, being
5 equipped with auxiliary openings or with a two-piece cannula opening, this to provide a certain turbulence when injecting.

There are also cannulae on the market the cutting edge of which is displaced by grinding to a point between the
10 periphery and the light opening.

It is an object of the present invention to improve known technology, and the invention, thus, relates to a cannula
15 with a bevelled point which forms a cutting edge, and the cannula is characterized by the fact that the cutting edge of the point extends along the light opening of the cannula in the portion which is placed furthest from the skin when the cannula is inserted.

20 Experiments proved that the cannula according to the invention results in a smaller penetration or wound area than known cannulae.

25 This was confirmed in tests on patients, up to 90% of whom said on inquiry that piercing with the cannula according to the invention caused less discomfort than piercing with cannulae of known technology. The tests were made with masked cannulae, one of each kind and one on each arm of the same
30 patient.

Another advantage which is achieved with the cannula according to the invention is that the cannula opening will face the stream when inserted into the vene, which will
35 provide a more rapid "backflow" and, thus, confirmation that the cannula is in place.

Other advantages of the invention will appear from the following disclosure with reference to the accompanying drawings, in which:

- 5 Figure 1 shows a conventional cannula with a cannula tube
 1 and a point 2;
- Figure 2 shows an enlarged portion of the point area of
 Figure 1;
- 10 Figure 3 shows a conventional cannula in a position for
 penetration;
- Figure 4 shows the situation in case of unintentional
15 penetration of the opposite vene wall;
- Figure 5 shows the unintended situation occurring when
 the cannula tube is wrongly placed;
- 20 Figure 6 shows an unintentional perforation of the
 cannula tube by the pont of the cannula;
- Figure 7 shows the general position of the point of the
 cannula according to the invention (compare with
25 Figure 2);
- Figure 8 corresponds to Figure 3, but shows the invent-
 ion;
- 30 Figure 9 basically corresponds to Figure 4, but shows the
 advantage achieved by the invention;
- Figure 10 and
 Figure 11 show a preferred embodiment of the invention
35 (compare with Figure 7);

Figure 12 shows the preferred embodiment and corresponds to Figure 9;

Figure 13 shows the preferred embodiment and corresponds to Figure 6;

5

As mentioned above all cannulae on the market at present are of the kind as shown in Figure 1, designed as shown in Figure 2 with the edge of the point being provided in the part of the cannula wall that is intended to lie in contact with the skin when used.

10

This is diagrammatically shown in Figure 2, and the accidents that may occur when the cannula is used are illustrated in Figures 3 - 6.

15

In Figure 3 cannula 1 with point area 2 and the associated plastic tube 7 is positioned to penetrate the skin 8 and vene 9 by also piercing one vene wall 9b.

20

Figure 4 shows what may happen if the cannula is inserted too steeply or forcefully. The opposite vene wall 9c is pictured, which will cause a hazard of blood oozing out of the vene with a consequent haematoma. The patient, thus, must be pierced once more.

25

In use, blood and medicament may then ooze out of opening 9c, so that there is also an accumulation of liquid outside the vene with further hazard of injuries to tissue and necrosis, see Figure 5.

30

Figure 6 shows a situation which may occur due to the fact that the point of the cannula is moved inside the cannula tube, the latter may be punctured at 7a.

35

As mentioned above, it is an object of the invention to remedy the shortcomings of known technology, and according to the general design of the invention this is achieved by

placing the cutting edge 3 of the cannula point 2 along the portion of the cannula wall which is intended to face away from the skin in use.

5 Generally, the cutting edge is achieved by simple angular cutting of the cannula, however it is possible both on conventional cannulae and on cannulae according to the invention to sharpen the cutting cannula edge, as indicated in Figure 2, so as to provide a regular point 4 in stead of
10 the present oval arch.

The cannula according to the invention is illustrated in Figures 8 and 9 with Figure 8 corresponding to Figure 3 immediately before the skin is punctured.

15 In Figure 9 the situation shown is immediately after cannula 1 with plastic tube 7 has penetrated the skin 8 and one vene wall 9a. It will appear that by placing the cutting edge according to the invention a more flat "underside" of the
20 point area 2 is achieved, which will substantially reduce the hazard of puncturing the other vene wall 9b, as shown in Figure 4.

The embodiment shown in Figures 7 - 9 represents an essential
25 improvement as compared to known technology, as illustrated in Figures 3 - 6.

There is, however, a certain though strongly reduced hazard of unintentional penetration of a vene wall upon insertion of
30 the cannula, also in connection with the object of the present invention. This is shown directly in Figure 4, but even after successful insertion a puncture may occur on the side where the point of the cannula is placed.

35 The preferred embodiment of the invention, as mentioned above, should solve this problem too, and this is the case with the embodiment generally shown in Figure 10.

6

It is achieved by reshaping the point area 2 to move the cutting edge 3 of the cannula from the outer diameter to the inner diameter or light opening, indicated by numeral 6 in Figures 7 and 10.

5

By moving the cutting edge 3 the hazard of unintentionally puncturing the vene wall is substantially reduced, as there is provided a further surface 11 as will appear, e.g. from Figure 12. Said surface may slide against the vene wall preventing the point from getting caught in the vene wall and unintentionally puncturing the wall.

10

According to the invention as disclosed above a cannula is achieved in a simple and inexpensive manner, and safety in operation and use is enhanced without sacrificing the safety of known cannulae and, additionally, without causing essentially increased costs.

15

The invention, thus, represents an essential improvement as regards operation and use of cannulae in connection with puncturing and cannulation of venes.

20

25

30

35

PATENT CLAIM:

A cannula (1) with a bevelled point (2) which forms a cutting
edge (3), c h a r a c t e r i z e d i n that the
5 cutting edge of point (2) extends along the portion of the
light opening (6) of the cannula which, in use, is intended
to be placed furthest away from the skin (8).

10

15

20

25



30

35





AMENDED CLAIMS

[received by the International Bureau
on 6 February 1992 (06.02.92);
original claim 1 replaced by amended claim 1
(1 page)]

Cannula (1) with a bevelled point (2) which forms a cutting edge (3), characterized in that the cutting edge (3) of the point (2) extends along the portion of the light opening (6) of the cannula (1) which, before the penetration of the skin (8), is furthest away from the skin (8).



2/4



SUBSTITUTE SHEET

3/4

Fig. 7




Fig. 8





Fig. 9



SUBSTITUTE SHEET

4/4

Fig 10




Fig.11




Fig.12








Fig.13



SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International Application No PCT/NO 91/00104

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ⁶ According to International Patent Classification (IPC) or to both National Classification and IPC IPC5: A 61 M 5/158, 5/32																	
II. FIELDS SEARCHED <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black;">Minimum Documentation Searched⁷</div> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%; border-bottom: 1px solid black;">Classification System</td> <td style="border-bottom: 1px solid black;">Classification Symbols</td> </tr> <tr> <td style="height: 40px; vertical-align: bottom;">IPC5</td> <td style="height: 40px; vertical-align: bottom;">A 61 M</td> </tr> </table> <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black;">Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in Fields Searched⁸</div> <p>SE,DK,FI,NO classes as above</p>			Classification System	Classification Symbols	IPC5	A 61 M											
Classification System	Classification Symbols																
IPC5	A 61 M																
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹ <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">Category *</th> <th style="width: 60%;">Citation of Document,¹¹ with indication, where appropriate, of the relevant passages¹²</th> <th style="width: 30%;">Relevant to Claim No.¹³</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">X</td> <td>GB, A, 1298707 (SIEMENS AKTIENGESellschaft) 6 December 1972, see page 2, line 66 - line 101; figures 1-2 --</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="text-align: center;">X</td> <td>DE, C, 346472 (METZ) 31 December 1921, see page 1, line 43 - line 53; figures 1-3 --</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="text-align: center;">X</td> <td>US, A, 2524713 (N.P. PLECHAS) 3 October 1950, see figure 1 --</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="text-align: center;">X</td> <td>US, A, 4368730 (SHARROCK) 18 January 1983, see figure 7 --</td> <td style="text-align: center;">1</td> </tr> </tbody> </table>			Category *	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³	X	GB, A, 1298707 (SIEMENS AKTIENGESellschaft) 6 December 1972, see page 2, line 66 - line 101; figures 1-2 --	1	X	DE, C, 346472 (METZ) 31 December 1921, see page 1, line 43 - line 53; figures 1-3 --	1	X	US, A, 2524713 (N.P. PLECHAS) 3 October 1950, see figure 1 --	1	X	US, A, 4368730 (SHARROCK) 18 January 1983, see figure 7 --	1
Category *	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³															
X	GB, A, 1298707 (SIEMENS AKTIENGESellschaft) 6 December 1972, see page 2, line 66 - line 101; figures 1-2 --	1															
X	DE, C, 346472 (METZ) 31 December 1921, see page 1, line 43 - line 53; figures 1-3 --	1															
X	US, A, 2524713 (N.P. PLECHAS) 3 October 1950, see figure 1 --	1															
X	US, A, 4368730 (SHARROCK) 18 January 1983, see figure 7 --	1															
<div style="display: flex; justify-content: space-between;"> <div style="width: 48%;"> <p>* Special categories of cited documents:¹⁰</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 48%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p> </div> </div>																	
IV. CERTIFICATION <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; border-bottom: 1px solid black;">Date of the Actual Completion of the International Search</td> <td style="width: 50%; border-bottom: 1px solid black;">Date of Mailing of this International Search Report</td> </tr> <tr> <td style="height: 40px; vertical-align: bottom;">29th November 1991</td> <td style="height: 40px; vertical-align: bottom;">1991 -12- 06</td> </tr> <tr> <td style="border-bottom: 1px solid black;">International Searching Authority</td> <td style="border-bottom: 1px solid black;">Signature of Authorized Officer</td> </tr> <tr> <td style="height: 40px; vertical-align: bottom; text-align: center;">SWEDISH PATENT OFFICE</td> <td style="height: 40px; vertical-align: bottom; text-align: center;">  Folke Svensson </td> </tr> </table>			Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	29th November 1991	1991 -12- 06	International Searching Authority	Signature of Authorized Officer	SWEDISH PATENT OFFICE	 Folke Svensson							
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report																
29th November 1991	1991 -12- 06																
International Searching Authority	Signature of Authorized Officer																
SWEDISH PATENT OFFICE	 Folke Svensson																

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No
X	US, A, 4642101 (KROLIKOWSKI ET AL) 10 February 1987, see column 2, line 60 - column 3, line 3; figures 3-5 --	1
A	SE, C, 135689 (AKTIEBOLAGET STILLE-WERNER) 13 May 1952, see page 2, column 1, line 30 - line 50; figure 3 --	1
A	DE, A, 2005519 (ROESCHEISEN & CO SÜDDEUTSCHE BINDENFABRIK) 28 October 1971, see page 10, line 5 - page 11, line 16; figures 1-2 --	1
A	US, A, 2187259 (G. E. BARNHART) 16 January 1940, see page 2, column 2, line 24 - line 28; figure 3 --	1
A	US, A, 2601580 (B.J. YANUS) 24 June 1952, see column 1, line 52 - column 2, line 4; figures 1,4-5 --	1
A	US, A, 4808170 (THORNTON ET AL) 28 February 1989, see column 3, line 10 - line 28; figures 4-5 -- -----	1

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO. PCT/NO 91/00104**

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.
The members are as contained in the Swedish Patent Office EDP file on 31/10/91
The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB-A- 1298707	72-12-06	CH-A- 501410 DE-A-B-C 1927868 FR-A- 2048823	71-01-15 70-12-03 71-03-19
DE-C- 346472	21-12-31	NONE	
US-A- 2524713	50-10-03	NONE	
US-A- 4368730	83-01-18	NONE	
US-A- 4642101	87-02-10	NONE	
SE-C- 135689	52-05-13	NONE	
DE-A- 2005519	71-10-28	NONE	
US-A- 2187259	40-01-16	NONE	
US-A- 2601580	52-06-24	NONE	
US-A- 4808170	89-02-28	NONE	